

## DalRollo

‘All the performance qualities of a Dalsouple floor in roll format.’



Our 16 gorgeous DalRollo solid colours are available in 12 metre long rolls of soft tactile Dalsouple rubber.

### Colour availability

DalRollo is available in 16 solid colours.

### Finish

Very lightly textured surface that gives the impression of a smooth floor, yet reduces glare from lighting.

### Roll size

12m x 1.22m.  
Available in full rolls only.\*

### Thickness

DalRollo rolls are 2mm thick.

### Performance

Anti-slip  
Anti-static  
Noise absorbent  
Cigarette burn resistant  
Tough  
Easy to maintain

### Uses

Indoor surfaces and floors,

### Slip resistance

DalRollo complies with the R9 slip resistance test.

Dalsouple rubber is designed to offer a good degree of slip resistance underfoot in dry conditions. However, it can still be slippery when wet. To minimise the risk of slippage, it is important to use effective entrance matting around all external entrances, and to use signs when cleaning takes place.

### Special colours

Please note that DalRollo is available in the 16 colours shown. The Dalsouple special colour matching service does not apply. For a custom colour floor, see DalUni floor tiles.

For **Colour reproduction**, **Technical**, **Standards & certification**, and **Samples & information** please see insert back.

### Colour reproduction

The colour samples are designed to give you an accurate representation of colour. However, you should note that due to the manufacturing process, colours may vary slightly from batch to batch. Also, as with any type of colour sampling, the colours may be subject to slight variation over time. The folder should be renewed periodically to maintain accurate colour communication.

### Technical

For information on installation, maintenance, adhesives and accessories please visit [dalsouple.com](http://dalsouple.com) or email [specs@dalsouple.com](mailto:specs@dalsouple.com)

### Standards & certification

DalRollo roll form rubber flooring in all colourways shown meets European standards in all key performance areas including dimensional stability, wear resistance, slip resistance, burn and fire resistance and sound absorption. For full details of test results visit [dalsouple.com](http://dalsouple.com) or email [tests@dalsouple.com](mailto:tests@dalsouple.com)

### Samples & information

[www.dalsouple.com](http://www.dalsouple.com)

### Questions?

email [info@dalsouple.com](mailto:info@dalsouple.com)  
tel +44 (0) 1278 727777  
fax +44 (0) 1278 727788



see [www.floorsymbols.com](http://www.floorsymbols.com)

## DALSOUPLE

Showground Road, Bridgwater, Somerset TA6 6AJ England  
tel +44 (0)1278 727777 fax +44 (0)1278 727788  
email [info@dalsouple.com](mailto:info@dalsouple.com) [www.dalsouple.com](http://www.dalsouple.com)

\*Dalsouple reserves the right to ship shorter roles (from 6 to 11.9m) to make up the full amount of the order. These shorter roles will not exceed 10% of the total order.

DalRollo is available in 16 colours.



Lait



Yaourt



Faon



Miel



Chantilly



Gelée



Jade




Laurier




Nuage



Rivière



Marlin



Calcaire



Brume



Gravier



Jais



Sang

DalRollo products are available in the colours shown. The Dalsouple colour matching system does not apply to DalRollazzo products.